This listing of claims will replace all prior versions, and listings, cf claims in the application:

- 1 Claim 1 (currently amended): For use with a node, a
- 2 method comprising:
- 3 accepting, using the node, status information
- 4 from at least two different protocols;
- 5 b) composing, using the node, an aggregated message
- 6 including the status information from the at least
- 7 two different protocols as data within the
- 8 aggregated message; and
- 9 c) sending, using the node, the aggregated message
- 10 towards a neighbor node.
- 1 Claim 2 (currently amended): The method of claim 1
- 2 further comprising:
- 3 d) maintaining, using the node, a first timer for
- 4 tracking a send time interval, wherein the acts of
- 5 composing the aggregated message and sending the
- 6 aggregated message are performed after expiration of
- 7 the first timer; and
- 8 e) restarting, using the node, the first timer
- 9 after the aggregated message is sent.
- 1 Claim 3 (previously presented): The method of claim 2
- 2 wherein the aggregated message further includes a dead
- 3 time interval, and wherein the send time interval is less
- 4 than the dead time interval.
- 1 Claim 4 (previously presented): The method of claim 2
- 2 wherein the aggregated message further includes a dead

- 3 time interval, and wherein the send time interval is no
- 4 more than one third of the dead time interval.
- 1 Claim 5 (original): The method of claim 2 wherein the
- 2 send time interval is less than one second.
- 1 Claim 6 (original): The method of claim 2 wherein the
- 2 send time interval is less than 100 msec.
- 1 Claim 7 (previously presented): The method of claim 1
- 2 wherein the aggregated message further includes a dead
- 3 time interval.
- 1 Claim 8 (previously presented): The method of claim 1
- 2 wherein the act of sending the aggregated message
- 3 includes providing the aggregated message in an Internet
- 4 protocol packet.
- 1 Claim 9 (previously presented): The method of claim 8
- 2 wherein the act of sending the aggregated message towards
- 3 the neighbor node includes setting a destination address
- 4 in the Internet protocol packet to a multicast address
- 5 associated with routers that support aggregated protocol
- 6 liveness.
- [Claim 10 (original): The method of claim 1 wherein the
- 2 neighbor rode has at least one protocol peering with at
- 3 least one of the at least two protocols.
- 1 Claim 11 (original): The method of claim 1 wherein the
- 2 status information includes a protocol state selected
- 3 from a group of protocols states consisting of (A)

```
protocol up, (B) protocol down, (C) protocol not
   reporting, and (D) protocol restarting.
   Claim 12 (currently amended): For use with a node, a
1
   method comprising:
2
        a) receiving, using the node, an aggregated message
3
4
        including
              i) for a first set of at least two different
5
              protocols of a neighbor node, status
6
              information for each of the protocols of the
7
              first set of the at least two different
8
              protocols as data within the aggregated
9
              message, and
10
              ii) a time interval; and
11
        b) updating, using the node, neighbor node protocol
12
         status information using the aggregated message.
13
    Claim 13 (currently amended): The method of claim 12
    wherein the act of updating neighbor node protocol status
    information includes
 3
              i) setting, using the node, a first timer to
 4
              the time interval and starting the first timer,
 5
              ii) if the first timer expires, setting, using
 6
              the node, the status of each of the protocols
 7
              of the neighbor node to down, and
 8
              iii) if a further message, sourced from the
 9
              neighbor node, and including
10
                       for a second set of at least two
11
                   protocols, status information for each of
12
                   the protocols of the second set, and
13
                    B) a new time interval,
14
```

15	is received then, resetting, using the node,
16	the first timer to the new time interval and
17	restarting the first timer.
1	Claim 14 (original): The method of claim 13 wherein each
2	of the time interval and the new time interval is less
3	than one second.
1	Claim 15 (original): The method of claim 12 wherein the
2	status information includes a protocol state selected
3	from a group of protocols states consisting of (A)
4	protocol up, (B) protocol down, (C) protocol not
5	reporting, and (D) protocol restarting.
1	Claim 16 (currently amended): The method of claim 13
2	wherein the act of updating neighbor node protocol status
3	information further includes
4	<pre>iv) if the further message is received then,</pre>
5	in addition to resetting the first timer to the
6	new time interval and restarting the first
7	cimer, further
8	A) determining, using the node, whether
9	the first set of at least two protocols is
10	the same as the second set of at least two
11	protocols,
12	B) if the first set of at least two
13	protocols is determined to be the same as
14	the second set of at least two protocols,
15	then for each of the at least two
16	protocols of both the first and second
17	sets having a changed status, informing,
18	using the node, a locally running instance

19	of the protocol of the changed status of
20	its peer protocol of the neighbor node,
21	and
22	C) if the first set of at least two
23	protocols is determined to be different
24	from the second set of at least two
25	protocols, then
26	 for any protocol in the second
27	set but not in the first set,
28	informing, using the node, a locally
29	running instance of the protocol of
30	the status indicated in the further
31	message of its peer protocol of the
32	neighbor node, and
33	2) for any protocol in the first set
34	but not in the second set, informing,
35	using the node, a locally running
36	instance of the protocol that the
37	status of its peer protocol of the
38	neighbor node is down.
1	Claim 17 (currently amended): The method of claim 16
2	wherein each of the aggregated message and the further
3	message include an indication of a relative message age,
4	and wherein the act of updating neighbor node protocol
5	status information includes,
6	iv) if the further message is received then,
7	on addition to resetting the first timer to the
8	r.ew time interval and restarting the first
9	timer, further

10	A) determining, using the node, whether
11	the further message is younger than the
12	aggregated message, and
13	B) if it is determined that the further
14	message is not younger than the aggregated
15	message, then discarding, using the node,
16	the further message.
1	Claim 18 (currently amended): The method of claim 13
2	wherein each of the aggregated message and the further
3	message include an indication of a relative message age,
4	and wherein the act of updating neighbor node protocol
5	status information includes,
6	<pre>iv) if the further message is received then,</pre>
7	in addition to resetting the first timer to the
8	rew time interval and restarting the first
9	timer, further
10	A) determining, using the node, whether
11	the further message is younger than the
12	aggregated message, and
13	B) if it is determined that the further
14	message is not younger than the aggregated
15	message, then discarding, using the node,
16	the further message.
1	Claim 19 (previously presented): A method for monitoring
2	liveness of multiple protocols, the method comprising:
3	a) determining, at a first node, status information
4	for at least two different protocols;
5	b) sending, from the first node, an aggregated
6	message including the determined status information

7

5

```
for the at least two different protocols as data
 8
         within the aggregated message to a second node;
 9
         c) receiving, at the second node, the aggregated
10
         message; and
11
         d) updating, by the second node, first node
12
         protocol status information using the aggregated
13
         message.
 1
    Claim 20 (previously presented): The method of claim 19
 2
    wherein the aggregated message further includes a first
    time interval, and wherein the act of updating neighbor
 3
    node protocol status information includes
 4
 5
              i) setting a timer to the first time interval;
 6
              ji) starting the timer;
 7
              iii) determining whether or not a further
 8
              message including protocol status information
 9
              is received from the first node by the second
10
              node before the expiration of the timer; and
11
                   if it is determined that a further message
12
              including protocol status information is not
13
              received from the first node by the second node
14
              before the expiration of the timer, then
15
              informing peer protocols of the second node
16
              that the at least two protocols of the first
17
              node are down.
   Claim 21 (original): The method of claim 19 wherein the
1
2
   status information includes a protocol state selected
   from a group of protocols states including at least (A)
3
4
   protocol up, (B) protocol down, (C) protocol not
```

reporting, and (D) protocol restarting.

```
Claim 22 (previously presented): A machine-readable
  1
  2
     medium having stored thereon a machine readable
     aggregated message comprising:
 4
          a) status information, for at least two different
 5
         protocols of a node, of a state of each of the at
         least two protocols stored as data within the
 7
         aggregated message; and
         b) a dead interval.
    Claim 23 (previously presented): The machine-readable
 1
    medium of claim 22 wherein the status information
 2
    indicates a protocol state selected from a group of
 3
    protocols states consisting of (A) protocol up, (B)
    protocol down, (C) protocol not reporting, and (D)
 5
    protocol restarting.
    Claim 24 (original): The machine-readable medium of
 1
   claim 22 further comprising:
2
3
        c) an identifier of the node.
   Claim 25 (criginal): The machine-readable medium of
1
   claim 24 wherein the node is a router and wherein the
   identifier is a router identifier.
1 Claim 26 (original): The machine-readable medium of
2 claim 22 further comprising:
        c) an interface index.
   Claim 27 (currently amended): For use with a node,
1
2
   [[elements] apparatus comprising:

 a) at least one processor;

       b) at least one input device; and
```

```
5
           c) at least one storage device storing
  6
           processor-executable instructions which, when
  7
           executed by one or more processors, perform a method
  8
           including
  9
                [[a]] \underline{i}) [[means for]] accepting status
 10
                information from at least two different
 11
                protocols[[+]],
 12
                [[b]] \underline{ii}) [[means-for]] composing an
13
                aggregated message including the status
14
                information from the at least two different
15
               protocols as data within the aggregated
16
                message[[+]] , and
17
               [[e]] <u>iii</u>) [[means for for]] sending the
18
               aggregated message towards a neighbor node.
    Claim 28 (currently amended): The [[elements]] apparatus
 1
    of claim 27 wherein the method further includes
 2
 3
     [[eomprising:]]
 4
          [[d]] \underline{iv}) [[means-for]] maintaining a first timer
 5
          for tracking a send time interval, wherein the
 6
          [[means for]] act of composing the aggregated
 7
         message and sending the aggregated message compose
 8
         and send the aggregated message after expiration of
9
         the first timer[[+]] \underline{\ \ } and
         [[e]] \underline{v}) [[meens for]] restarting the first timer
10
11
         after the aggregated message is sent.
    Claim 29 (currently amended): The [[elements]] apparatus
1
   of claim 28 wherein the aggregated message further
2
    includes a dead time interval, and wherein the send time
3
    interval is less than the dead time interval.
```

- l Claim 30 (currently amended): The [[elemente]] apparatus
- 2 of claim 28 wherein the aggregated message further
- 3 includes a dead time interval, and wherein the send time
- 4 interval as no more than one third of the dead time
- 5 interval.
- 1 Claim 31 (currently amended): The [[elements]] apparatus
- 2 of claim 78 wherein the send time interval is less than
- 3 one seconc.
- 1 Claim 32 (currently amended): The [[elements]] apparatus
- 2 of claim 28 wherein the send time interval is less than
- 3 100 msec.
- 1 Claim 33 (currently amended): The [[elements]] apparatus
- 2 of claim 27 wherein the aggregated message further
- 3 includes a dead time interval.
- 1 Claim 34 (currently amended): The [[elements]] apparatus
- 2 of claim 27 wherein the [[means for]] act of sending the
- 3 aggregated message includes [[include means for]]
- 4 providing the aggregated message in an Internet protocol
- 5 packet.
- 1 Claim 35 (currently amended): The [[elements]] apparatus
- 2 of claim 34 wherein the [[means for]] act of sending the
- 3 aggregated message <u>includes</u> [[include means for]] setting
- 4 a destination address in the Internet protocol packet to
- 5 a multicast address associated with routers that support
- 6 aggregated protocol liveness.

l

```
Claim 36 (currently amended): The [[elements]] apparatus
     of claim .27 wherein the neighbor node has at least one
    protocol peering with at least one of the at least two
 3
    protocols.
    Claim 37 (currently amended): The [[elements]] apparatus
    of claim 27 wherein the status information includes a
 2
    protocol state selected from a group of protocols states
 4 consisting of (A) protocol up, (B) protocol down, (C)
 5. protocol rot reporting, and (D) protocol restarting.
 1
    Claim 38 (currently amended): For use with a node,
 2
    [[elements]] apparatus comprising:
 3
          a) at least one processor;
 4
          b) at least one input device; and
 5
          c) at least one storage device storing
 6
         processor-executable instructions which, when
 7
         executed by one or more processors, perform a method
 8
         including
 9
         [[a]] i) [[an input for]] receiving, using the at
10
         least one input, an aggregated message including
11
               [\{\frac{1}{2}\}] \underline{A}) for a first set of at least two
12
              different protocols of a neighbor node, status
13
              information for each of the protocols of the
14
              first set of the at least two different
15
              protocols as data within the aggregated
16
              message, and
17
              \{\frac{1}{2}\} B) a time interval\{\{\frac{1}{2}\}\}, and
18
         [[b]] <u>ii</u>) [[means for]] updating neighbor node
19
         protocol status information using the aggregated
20
         messace.
```

```
Claim 39 (currently amended): The [[elements]] apparatus
   of claim 38 wherein the [[means for]] act of updating
   neighbor node protocol status information [[include]]
4
   includes
5
              [[i]] A) [[means-for]] setting a first timer
6
              to the time interval and starting the first
7
              timer,
8
              [[ii]] B) [[means for]] setting the status of
9
              each of the protocols of the neighbor node to
              down if the first timer expires, and
10
              [iii]] C) [[means,]] if a further message,
11
              sourced from the neighbor node, and including
12
                   [[A]] 1) for a second set of at least two
13
                   protocols, status information for each of
14
15
                   the protocols of the second set, and
16
                 [[B]] 2) a new time interval,
17
              is received, [[for]] resetting the first timer .
              to the new time interval and restarting the
18
19
              first timer.
   Claim 40 (currently amended): The [[elements]] apparatus
1
2 of claim 39 wherein each of the time interval and the new
   time interval is less than one second.
   Claim 41 (currently amended): The [[elements]] apparatus
   of claim 33 wherein the status information includes a
   protocol state selected from a group of protocols states
    consisting of (A) protocol up, (B) protocol down, (C)
   protocol not reporting, and (D) protocol restarting.
```

Claim 42 (currently amended): The [[elements]] apparatus
of claim 39 wherein the [[means for]] act of updating

```
neighbor node protocol status information further
  3
     [[information-include]] includes
  4
  5
                [[i*) means for]]
  6
                [[A]] \underline{D}) determining whether the first set of
 7
                at least two protocols is the same as the
  8
                second set of at least two protocols,
 9
                [[B]] E) if the first set of at least two
 10
                protocols is determined to be the same as the
11
                second set of at least two protocols, then for
12
                each of the at least two protocols of both the
13
                first and second sets having a changed status,
14
                informing a locally running instance of the
15
               protocol of the changed status of its peer
16
               protocol of the neighbor node, and
17
                [[\Theta]] F) if the first set of at least two
18
               protocols is determined to be different from
19
               the second set of at least two protocols,
20
                    1) for any protocol in the second set but
21
                    not in the first set, informing a locally
22
                    running instance of the protocol of the
23
                    status indicated in the further message of
24
                    its peer protocol of the neighbor node,
25
                    and
26
                    2)
                        for any protocol in the first set but
27
                    not in the second set, informing a locally
28
                    running instance of the protocol that the
29
                   status of its peer protocol of the
30
                   neighbor node is down.
```

¹ Claim 43 (currently amended): The [[elements]] apparatus

² of claim 42 wherein each of the aggregated message and

³ the furthem message include an indication of a relative

```
4
    message age, and wherein the [[means for]] act of
    updating neighbor node protocol status information
 5
     [[includes,
 7
               [[<del>iv] means for</del>]]
 8
                [[A]] \underline{D}) determining whether the further
 9
               message is younger than the aggregated
10
               message, and
11
                [[B]] E) if it is determined that the further
12
               message is not younger than the aggregated
13
              . message, then discarding the further message.
14
    Claim 44 (currently amended): The [[elements]] apparatus
 2^{\circ} of claim 19 wherein each of the aggregated message and
   the further message include an indication of a relative
    message age, and wherein the [[means for]] act of
    updating neighbor node protocol status information
 6 [[include]] includes,
 7
               [[<del>iv) means for</del>]]
8
               [[A]] D) determining whether the further
9
               message is younger than the aggregated
10
               message, and
11
               [B] \underline{E} if it is determined that the further
12
               message is not younger than the aggregated
13
               message, then discarding the further message.
1
    Claim 45 (previously presented): A system comprising:
2
         a)
              a first node adapted to
3
                  determine status information for at least
4
              two different protocols, and
5
              Ĺi)
                   send an aggregated message including the
6
              determined status information for the at least
```

7

```
two different protocols as data within the
  8
               aggregated message to a second node; and
 9
          b) the second node adapted to
 10
               i) receive the aggregated message; and
 11
               ii) update first node protocol status
12
               information using the aggregated message.
    Claim 46 (previously presented): The system of claim 45
 1
 2
    wherein the aggregated message further includes a first
    time interval, and wherein the act of updating the first
 3
 4
    node protocol status information includes
 5
                        setting a timer to the first time
                    A)
 6
                    interval;
 7
                    B) starting the timer;
                        determining whether or not a further
 9
                    message including protocol status
10
                    information is received from the first
11
                    node by the second node before the
12
                    expiration of the timer; and
13
                        if it is determined that a further
14
                   message including protocol status
15
                   information is not received from the first
16
                   node by the second node before the
17
                   expiration of the timer, then informing
18
                   peer protocols of the second node that the
19
                   at least two protocols of the first node
20
                   are down.
```

- Claim 47 (criginal): The system of claim 46 wherein the 1
- 2 status information includes a protocol state selected
- 3 from a group of protocols states including at least (A)

- 4 protocol up, (B) protocol down, (C) protocol not
- 5 reporting, and (D) protocol restarting.
- 1 Claim 48 (previously presented): The method of claim 1
- 2 wherein the status information is local protocol status
- 3 information.
- 1 Claim 49 (previously presented): The method of claim 1
- 2 wherein the status information is local status
- 3 information and wherein each of the at least two
- 4 different protocols is bring run locally on the node.
- 1 Claim 50 (new): The method of claim 1 wherein the status
- 2 information of at least one of the at least two different
- 3 protocols included in the aggregated message includes a
- 4 protocol state set to protocol not reporting.
- 1 Claim 51 (new): The method of claim 1 wherein the status
- 2 information of at least one of the at least two different
- 3 protocols included in the aggregated message includes a
- 4 protocol state set to protocol restarting.
- 1 Claim 52 (new): The method of claim 12 wherein the
- 2 status information of at least one of the at least two
- 3 different protocols included in the first set of at least
- 4 two different protocols included within the aggregated
- 5 message includes a protocol state set to protocol not
- 6 reporting,
- 1 Claim 53 (new): The method of claim 12 wherein the
- 2 status information of at least one of the at least two
- 3 different protocols included in the first set of at least

- 4 two different protocols included within the aggregated
- 5 message includes a protocol state set to protocol
- 6 restarting.